



# Installation Tools and Accessories

Self-igniting Propane-fired Torch




## PROPANE TORCH

**PFT-1016 HS** Self-igniting, clean-burning powerful flame for medium to large jobs. Recommended for installation of all high and low voltage products. Comes with 9/16-L.H.male thread end fitting for easy adaptation to standard propane hoses. Approximately 32,000 BTU/hour.

**Torch Only: Hose, regulator and tank not included.**

## PROPANE REGULATORS

LPG Regulator



**PR-1010** Regulator, fixed with tailpiece  
**PR-1030** Regulator, variable with guage (0-30 psi)  
**PR-1035** Regulator, fixed pressure, with end fitting for disposable propane cylinder and 3 foot hose, fixed at regulator

LPG Hoses



## PROPANE HOSES

**PH-1110** 10 foot long LPG hose with female threads each end  
**PH-1120** 20 foot long LPG hose with female threads each end

Hot Air Gun



**HAG-110** 110 volt Hot air gun for use on all low voltage products and most medium voltage accessories. **Not recommended for MV. Splices**  
**HAG-220** 220 volt Hot air gun for use on all low voltage products and most medium voltage accessories. **Not recommended for MV. Splices**

Blanket



**SH-1412** Heat shield: woven fabric with eyelets. Protects adjacent components from torch heat for safety: Size 12" X 40"

## SEALANTS



**SMB 202** Black sealing mastic for general sealing 0.5" W x 0.125"T x 12" L  
**SMB 205** Black sealing mastic for general sealing 1.0" W x 0.20"T x 12" L



**SMR 307** Red sealing material; 1.0" W x 0.25"T x 12" L  
**SMR 309** Red sealing material; 2.0" W x 0.035"T x 15" L



**FCM 90824** Field control/Oil-blocking material; 1.0" W x 0.06"T x 24" L

## SHIELDING MATERIAL



**MSH 2015** Tinned copper mesh width 2.50"; 15 foot roll  
**MSH 2030** Tinned copper mesh width 2.50"; 30 foot roll  
**MSH 2050** Tinned copper mesh width 2.50"; 50 foot roll

### Related Product Information

Torches and Sealants: • Price List PL-510